25 W car charger with MP3 / FM player and ambient ring

Cigar-lighter unit: 25 W USB-C PD charging, two USB-A ports, live voltage readout, MP3 playback from flash drive or over FM, fixed 1-to-2 spring cable with Lightning and USB-C.

SPECIFICATION

Model	C29 (factory code) · VX-C25-MP3 (house code)
Output	25 W max on USB-C (PD). USB-A port rated 3.1 A fast charge. Total across three ports stated on the quotation.
Ports	1× USB-C (PD) + 2× USB-A; one USB-A also reads a USB flash drive
Display	LED digital readout of the vehicle supply voltage
Light	RGB ambient ring around the panel, independent on/off button
Audio	MP3 playback from USB flash drive; FM transmit to car radio with channel (CH) button; rotary knob for track and volume
Spring cable	Fixed 1-to-2, Lightning + USB-C. Spare cables can be ordered as a separate accessory line; stretched length on the quotation.
Input	**12 V DC only.** Not for 24 V trucks or 24 V commercial vehicles — a 12/24 V body is a different build and is quoted separately.
Protection	Over-current, over-voltage, over-temperature, short circuit
Body	ABS + PC, black; cigar-lighter plug with spring contacts
Packing	Hanging retail box, insert, manual — printed to buyer artwork

Options on the line

- Spring cable: Lightning + USB-C, 2× USB-C, or single connector
- Ring light: fixed colour, breathing, or off by default
- Display: voltage only, or voltage plus charging status
- Shell colour, knob logo, retail box artwork

Confirmed on quotation

- Per-port allocation table and total output
- Bluetooth version if fitted, FM channel range
- Certification set held by C29, with report number and lab
- Net weight, carton quantity, MOQ, lead time, FOB port

BEFORE YOU STOCK IT

- **The spring cable is not user-replaceable.** Spare cables ship as a separate accessory line — confirm connector mix, stretched length and spare-cable MOQ.
- **FM quality depends on the local band.** Test on a real head unit in the destination market, not on a bench speaker.
- **Three ports share one budget.** 25 W is the USB-C ceiling; the split changes as ports are used.

Prices are per written quotation only. Images and figures are for reference; the approved sample prevails. Market admission, registration, labelling language and tariffs rest with the importer of record. Certification marks are printed only where the certificate exists for this model.