VOLTYX TECH
SPECIFICATION SHEET · 2026-11

Shenzhen / Guangzhou, China
WhatsApp +86 188 8200 0886
longweizhou41@gmail.com

65 W GaN wall charger, two USB-C ports

VX-G65-2C · 氮化镓充电器 · 65W · 双 USB-C



65 W | 2× USB-C | PD 3.0 | PPS | 100–240 V | GaN

Model 型号	VX-G65-2C
Output 输出	65 W max on one port; dual-port split stated on the quotation
Ports 接口	2× USB-C, or 1× USB-C + 1× USB-A (option)
Protocols 协议	PD 3.0, PPS, QC (BC 1.2)
Input 输入	100–240 V AC, 50/60 Hz
Plug 插脚	EU / UK / US / AU, fixed or interchangeable; folding pins on travel SKUs
Technology 技术	GaN (gallium nitride) switching stage
Protection 保护	Over-current, over-voltage, over-temperature, short circuit
Packing 包装	Retail box, insert, manual — to your artwork

CE | **FCC** | **RoHS** | **Level VI**

Size, net weight and carton quantity confirmed on the quotation and on the approved sample. Safety mark printed per market — plug type and certification are fixed together.

Price: per written quotation — unit price, MOQ, lead time and port confirmed on the quotation. **Packing:** retail box, insert and manual produced to your artwork. **Sample:** 1–2 units, cost credited to the bulk order.